

## CUTE-3-M

~25° medium beam with 1.5 mm high location pins


### TECHNICAL SPECIFICATIONS:

Dimensions	Ø 35 mm
Height	15 mm
Fastening	glue, pin
Colour	clear
Box size	480 x 280 x 300 mm
Box weight	6.8 kg
Quantity in Box	630 pcs
ROHS compliant	yes ⓘ



### MATERIAL SPECIFICATIONS:



Component	Type	Material	Colour
CUTE-3-M	Lens array	PMMA	clear




**PHOTOMETRIC DATA (MEASURED):**



LED XM-L  
FWHM 25.0°  
Efficiency 90 %  
Peak intensity cd/lm  
Required components:



LED XM-L2  
FWHM 26.0°  
Efficiency 89 %  
Peak intensity 3.700 cd/lm  
Required components:



LED XP-E  
FWHM 22.0°  
Efficiency 91 %  
Peak intensity cd/lm  
Required components:



LED XP-G  
FWHM 24.0°  
Efficiency 91 %  
Peak intensity cd/lm  
Required components:

## PHOTOMETRIC DATA (MEASURED):

### **CREE**

LED XP-L  
FWHM 24.0°  
Efficiency 88 %  
Peak intensity 3.900 cd/lm  
Required components:



### **LUMILEDS**

LED LUXEON A  
FWHM 24.0°  
Efficiency %  
Peak intensity cd/lm  
Required components:

### **LUMILEDS**

LED LUXEON Rebel  
FWHM 22.0°  
Efficiency 91 %  
Peak intensity cd/lm  
Required components:


### **LUMILEDS**

LED LUXEON Rebel ES  
FWHM 24.0°  
Efficiency 92 %  
Peak intensity cd/lm  
Required components:

### PHOTOMETRIC DATA (MEASURED):



#### LUMILEDS

LED LUXEON T  
FWHM 23.0°  
Efficiency 89 %  
Peak intensity 4.200 cd/lm  
Required components:



#### LUMILEDS

LED LUXEON TX  
FWHM 25.0°  
Efficiency 88 %  
Peak intensity 4.300 cd/lm  
Required components:



#### NICHIA

LED NCSxx19A  
FWHM 25.0°  
Efficiency 88 %  
Peak intensity cd/lm  
Required components:

#### NICHIA

LED NVSxx19A  
FWHM 25.0°  
Efficiency 88 %  
Peak intensity cd/lm  
Required components:

## PHOTOMETRIC DATA (MEASURED):

**OSRAM**  
Opto Semiconductors



LED Oslon SSL 150  
FWHM 24.0°  
Efficiency %  
Peak intensity cd/lm  
Required components:

**OSRAM**  
Opto Semiconductors

LED Oslon SSL 80  
FWHM 22.0°  
Efficiency 89 %  
Peak intensity cd/lm  
Required components:

**TOSHIBA**  
Leading Innovation >>>

LED TL1L3  
FWHM 26.0°  
Efficiency 86 %  
Peak intensity 2.600 cd/lm  
Required components:



### PHOTOMETRIC DATA (SIMULATED):

#### CREE


LED XM-L HVW  
FWHM 33.0°  
Efficiency %  
Peak intensity cd/lm  
Required components:

#### CREE

LED XT-E HVW  
FWHM 30.0°  
Efficiency %  
Peak intensity cd/lm  
Required components:


#### LUMILEDS

LED LUXEON H50-2  
FWHM 30.0°  
Efficiency 90 %  
Peak intensity 2.700 cd/lm  
Required components:




#### NICHIA

LED NVSxx19B/NVSxx19C  
FWHM 30.0°  
Efficiency 89 %  
Peak intensity 2.530 cd/lm  
Required components:



## PHOTOMETRIC DATA (SIMULATED):





### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)