



All dimensions are in mm; tolerances acc. ISO 2768 m-H

**Documents**

Assembly instruction 29 E  
 Panel piercing B 31

**Material and plating**

**Connector parts**

Body Brass  
 Crimping sleeve Copper

**Plating**

Gold, 0.1 µm min.  
 Gold, 0.1 µm min.

**Environmental data**

RoHS compliant

**Tooling**

Crimping tool 11W150-000  
 Crimp insert 11W150-102

**Suitable cables**

RG 316 /U, RG 174 A/U, RG 188 A/U

**Weight**

Weight 0.61 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Inge Mühlauer	07/09/04	Sa. Krautenbacher	13.03.14	c00	14-0352	T. Krojer	13.03.14
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany <a href="http://www.rosenberger.de">www.rosenberger.de</a>					Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: <a href="mailto:info@rosenberger.de">info@rosenberger.de</a>		Page 2 / 2